

MONTUR S LED 930 B

232 112 93 B

AVAILABLE IN



ALU GREY 232 112 93 A

BLACK 232 112 93 B

FLEMISH BRONZE OUTDOOR 232 112 93 FBRX

ANTHRACITE (DARK GREY) 232 112 93 N

WHITE 232 112 93 W



[View on website](#)

General info

LOCATION	indoor-outdoor
INSTALLATION	Ceiling Surface mounted, Wall Surface mounted
INGRESS PROTECTION	IP65
PROTECTION AGAINST MECHANICAL IMPACT	IK07
WEIGHT (KG)	2,3
ADJUSTABILITY	non adjustable
INFORMATION	INCL.GLASS OPAL INCL.LED POWER SUPPLY 350mA-DC

Electrical info

ELECTRICAL	100-240V / 50-60Hz
CLASS	I
POWER SUPPLY INCLUDED	YES
DIM TYPE	non-dimmable
ENERGY CLASS	D
CERTIFICATES	CB

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED cluster 6,3W / CRI>90 (R9: 50) / 3000K / 925lm
TM-30 VALUES	Rf: 92 / Rg: 100
SDCM	SDCM3
RISKGROUP	RG2
LM80	L80 > 60000
LED TECHNICS (LIGHT SOURCE)	925lm // 6,3W // 147lm/W
LED TECHNICS (LUMINAIRE)	555lm // 7W // 77lm/W

For detailed installation instructions, please consult the manual: [232_112_XX_HAND.pdf](#)



MONTUR S LED 930 B

232 112 93 B

Notes: