



WEVER & DUCRÉ
LIGHTING

BOX WALL 2.0 LED

331148B9

GENERAL

Wall

Surface

Jet Black

IP20

Interior

Total 400 lm

9005^a

LED

1800 K - 2850 K

CRI 80

L90 / 50000 h

3-step binning

OPTICAL

spot

PHYSICAL

Length 100 mm

Width 100 mm

Height 100 mm

0.67 kg

ELECTRICAL

phase-cut dim

220 - 240 V

Total connected power 5.5 W

PC1

Safety distance 0.3 m

^a RAL Palette colors may deviate slightly due to production conditions.


Project

Type

Notes

Quantity

Date





WEVER & DUCRÉ
LIGHTING

BOX WALL 2.0 LED

331148B9

Maintenance Factors

Operating Time [h]	10 000	20 000	30 000	40 000	50 000
LLMF	0.97	0.95	0.93	0.91	0.9
LSF	1	1	1	1	1

MF	$LMF \times RSMF \times LLMF \times LSF$	RSMF ^a	Room Surface Maintenance Factor
MF	Maintenance Factor	LLMF	Lamp Lumens Maintenance Factor
LMF ^a	Luminaire Maintenance Factor	LSF	Lamp Survival Faktor

^a According to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.