

FLOS

06.2541.14 Black

Zero Track Surface Profile. Feed intermediate connector NEW


Designed by FLOS Architectural, 2020



Feed intermediate connector. Upper feeding cable entry.

Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)



Main specifications

Mounting	Surface
Environments	Indoor dry location
Light Source Type	LED
Iicos	No
Bulb finish	Clear

Physical


Colour	Black
Trim	No
Length (mm)	82
Net weight (kg)	0.01
IP internal	20

Download

[Mounting instructions](#)



Ecodesign and Energy Labelling



Replaceable control gear by a professional

Electrical

Insulation class	III
Main voltage (Vac)	24
LED voltage Vf (Vdc)	24.00

Notes

PWM voltage output dimmable drivers shall be used at frequencies between 250 and 500Hz.

Accessories & Power Supply



REQUIRED
Power supply

Electrical

60.9359

24V Remote power supply. 25W
110/240V



REQUIRED
Power supply

Electrical

60.9360

24V Remote power supply. 36W-
110V / 45W-240V



REQUIRED
Power supply

Electrical

60.9361

24V Remote power supply. 57W
220/240V



REQUIRED
Power supply

Electrical

60.9516

Remote Power Supply Non
Dimmable 24V. 120W. 220/240V



REQUIRED
Power supply

Electrical

60.9443

Remote Power Supply Non
Dimmable 24V. 100W. 220/240V



REQUIRED
Power supply

Electrical

60.9777

Remote Power Supply Non
Dimmable 24V. 120W. 220/240V



REQUIRED
Power supply

Electrical

60.9515

Remote Power Supply Non
Dimmable 24V. 60W. 220/240V



REQUIRED
Power supply

Electrical

60.9374

Remote Power Supply Non
Dimmable 24V. 60W. 220/240V