







In Vitro Unplugged





F018E21K018 - Deep Brown

 $Lighting\ device\ for\ exterior\ ground\ installation.\ Opalescent\ diffuser\ integrated\ in\ the\ head\ and\ outer\ protective\ glass\ in\ transparent\ borosilicate.$

The structural parts are made of die-cast and extruded aluminium treated with a chemical conversion process to protect against atmospheric agents. The body is powder coated with a range of available finishes. Integrated LED light source with Edge Lighting technology to guarantee perfectly uniform lighting. Portable version equipped with handle for transport. Dimmer driver 5/100–240 V/50-60 Hz integrated into the body of the device with optical touch sensor on the head to regulate the brightness in 4 steps: 100% - 50% - 3% - OFF. Rechargeable via micro USB-C cable, 120 cm long, guaranteeing continuous lighting up to 6 hours. IP20 charger with EUR, UK, USA interchangeable plugs.

Main specifications			
Lamp category Power (W) CCT (K) CRI Net lumen (lm)	LED 2.5W 2700K 90 103	Mountings Environment	Table Outdoor
Optical			
Lighting type LED type Light distribution Optical type Beam angle (°)	Direct Edge Lighting Symmetric Diffused light 111	Beam angle C90-270 (°)	111
Electrical			
Frequency (Hz) Voltage (V) Dimmable Driver Driver type	50-60 5/100÷240V Yes Integrated Dimmer on board	Emergency Insulation class	Without III
Physical			
Color Orientation Weight (kg)	Deep Brown Fixed 1		

Note

When setting up and maintaining the device, be particularly careful not to damage the powder coating. Damage combined with water may lead to corrosion.

Chemical products may damage the corrosion protection.