



WEVER & DUCRÉ
LIGHTING

TUBE 1.0 LED

734164W4

Project

Type

Notes

Quantity

Date

GENERAL

Ceiling

Surface

Signal White

IP65

Exterior

475 lm

9003^a

LED

3000 K

CRI 80

L70 / 50000 h

3-step binning

OPTICAL

Beam angle 33°

PHYSICAL

Diameter 80 mm

Height 105 mm

0.53 kg

ELECTRICAL

phase-cut dim

220 - 240 V

Total connected power 7.2 W


PC1

Safety distance 0.3 m


^a RAL Palette colors may deviate slightly due to production conditions.



IP65



LIGHT DISTRIBUTION



[734164W402] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré BVBA apply.
© Wever & Ducré BVBA · Spinnerijstraat 99/21 · 8500 Kortrijk · Belgium · www.weverducre.com



WEVER & DUCRÉ
LIGHTING

TUBE 1.0 LED

734164W4

CONE DIAGRAM

33°

h (m)	E0° (lx)	ø (m)
1	1270	0.60
2	318	1.19
3	141	1.79
4	79	2.38
5	50	2.98