





ORIS

OUTDOOR
WALL RECESSED



0.8

LED PCB 2/4W | 350/700mA | 6V
excl. driver
aluminium powder coated

IP65 SDCM3 L70/60K 0.16kg

66x66 40 min. 12

3000K | >90 CRI | 90/140lm

CODE

White	7094A1W5
Grey	7094A1A5
Dark Grey	7094A1Q5
Black	7094A1B5

1.3

LED PCB 3/6W | 350/700mA | 9V
excl. driver
aluminium powder coated

IP65 SDCM3 L70/60K 0.34kg

115x117 40 min. 12

3000K | >90 CRI | 140/220lm

CODE

White	7096A1W5
Grey	7096A1D5
Dark Grey	7096A1A5
Black	7096A1Q5
Black	7096A1B5

ALWAYS USE

driver | IP66

CODE

3W 350mA	90213101
7W 500mA	90214301
7W 700mA	90215301

more options and specs on page 736

ALWAYS USE

driver | IP66

CODE

3W 350mA	90213101
7W 500mA	90214301
7W 700mA	90215301

more options and specs on page 736

OPTIONAL

recessed housing incl. plasterkit

CODE

Black	90012047
-------	----------

concrete housing

CODE

Black	90012046
-------	----------

specs on page 748

OPTIONAL

recessed housing incl. plasterkit

CODE

Black	90012041
-------	----------

concrete housing

CODE

Black	90012040
-------	----------

specs on page 748

