




ORIS

OUTDOOR WALL RECESSED



0.7

LED PCB 2/4W | 350/700mA | 6V
excl. driver
aluminium powder coated

IP65 SDCM3 L70|60K 0.28kg

47x182 40 min. 12

3000K | >90 CRI | 70/115lm

	CODE
	7091A1W5
	7091A1D5
	7091A1B5

ALWAYS USE

driver | IP66

	CODE
3W 350mA	90213101
7W 500mA	90214301
7W 700mA	90215301

more options and specs on page 736

OPTIONAL


recessed housing incl. plasterkit

	CODE
	90012039

concrete housing

	CODE
	90012044

specs on page 748



2.0

LED PCB 3/6W | 350/700mA | 9V
excl. driver
aluminium powder coated

IP65 SDCM3 L70|60K 0.42kg

115x185 40 min. 12

3000K | >90 CRI | 140/220lm

	CODE
	7097A1W5
	7097A1D5
	7097A1B5

ALWAYS USE

driver | IP66

	CODE
3W 350mA	90213101
7W 500mA	90214301
7W 700mA	90215301

more options and specs on page 736

OPTIONAL

recessed housing incl. plasterkit

	CODE
	90012043

concrete housing

	CODE
	90012042

specs on page 748

