

## Global Trac Electrical Accessories

### GLOBAL TRAC PRO END FEED-L WHITE

### XTS12-3



#### Product features

- Global Trac Pro accessory - white, glass fibre reinforced polycarbonate end feed that is applicable for three-circuit track systems where the polarity ridge is in the left side. Dimensions - 105 x 32 x 33 mm (L x W x H).



## PRODUCT OVERVIEW

Product name	GLOBAL TRAC PRO END FEED-L WHITE
Technology	Accessory
Housing	PC Polycarbonate
General application	Retail
ETIM Class	EC002556
E-number SE	7402218
Warranty	5 years
Light colour	N/A
Dimmable	No
Housing colour	RAL 9010 - Pure white
IP rating	IP20
IK rating	IK02
Product EAN number	6410014507121

## DATA TABLE

### General data

Product name	GLOBAL TRAC PRO END FEED-L WHITE
Technology	Accessory
Housing	PC Polycarbonate
General application	Retail
Operating temperature range (°C)	0°C...+25°C
ETIM Class	EC002556
E-number SE	7402218
Warranty	5 years

### Optical data

Light colour	N/A
--------------	-----

### Electrical data

Mains voltage (V)	220-240V
-------------------	----------

## Global Trac Electrical Accessories

### GLOBAL TRAC PRO END FEED-L WHITE

### XTS12-3

Dimmable No

#### Physical data

Housing colour	RAL 9010 - Pure white
IP rating	IP20
IK rating	IK02
Nominal Product Length (mm)	105
Nominal Product Width (mm)	32
Nominal Product Height (mm)	33
Weight (kg)	0.053

#### Packaging

Single packaging type	Carton
Product EAN number	6410014507121
Packaging single length / height (cm)	9.9
Packaging single width (cm)	3.2
Packaging single depth (cm)	3.3
DUN14 (outer)	06410014507121
Units per outer package	1
Packaging outer length / height (cm)	9.9
Packaging outer width (cm)	3.2
Packaging outer depth (cm)	3.3

#### Safety data

Optimal operating condition (°C)	0-25
Special purpose lamp	No
Dry applications use only	Yes

## TECHNICAL DRAWINGS

