

Global Trac Electrical Accessories

GLOBAL TRAC PRO L FEED IN BLACK

XTS34-2



Product features

- Global Trac Pro accessory - black, glass fibre reinforced polycarbonate L-feed that is applicable for three-circuit track systems where the polarity ridge is in the inner side. Dimensions - 99 x 99 x 33 mm (L x W x H).



PRODUCT OVERVIEW

Product name	GLOBAL TRAC PRO L FEED IN BLACK
Technology	Accessory
Housing	PC Polycarbonate
General application	Retail
ETIM Class	EC002556
E-number SE	7402227
Warranty	5 years
Light colour	N/A
Dimmable	No
Housing colour	RAL 9005 - Jet black
IP rating	IP20
IK rating	IK02
Product EAN number	6410014506346

DATA TABLE

General data

Product name	GLOBAL TRAC PRO L FEED IN BLACK
Technology	Accessory
Housing	PC Polycarbonate
General application	Retail
Operating temperature range (°C)	0°C...+25°C
ETIM Class	EC002556
E-number SE	7402227
Warranty	5 years

Optical data

Light colour	N/A
--------------	-----

Global Trac Electrical Accessories

GLOBAL TRAC PRO L FEED IN BLACK

XTS34-2

Electrical data

Mains voltage (V)	220-240V
Dimmable	No

Physical data

Housing colour	RAL 9005 - Jet black
IP rating	IP20
IK rating	IK02
Nominal Product Length (mm)	99
Nominal Product Width (mm)	99
Nominal Product Height (mm)	33
Weight (kg)	0.094

Packaging

Single packaging type	Plastic
Product EAN number	6410014506346
Packaging single length / height (cm)	15.4
Packaging single width (cm)	24.4
Packaging single depth (cm)	3.2
DUN14 (outer)	06410014506346
Units per outer package	1
Packaging outer length / height (cm)	15.4
Packaging outer width (cm)	24.4
Packaging outer depth (cm)	3.2

Safety data

Optimal operating condition (°C)	0-25
Special purpose lamp	No
Dry applications use only	Yes

TECHNICAL DRAWINGS

