




## MINI-PI 1 UP



### Material

aluminium

### Materiaal

aluminium

### Matériau

aluminium



### Finish

black - grey - white  
lens : PMMA

### Afwerking

zwart - grijs - wit  
lens : PMMA

### Finition

noir - gris - blanc  
lentille : PMMA

### Lightsource

4 x power LED (included) 1.2W  
cold white : 6000K - 440lm - CRI >75  
4 x LED (included) 0.96W  
warm white : 2700K - 456lm - CRI >93  
beam : 10° - 25° - 40°

### Lichtbron

4 x power LED (inclusief) 1.2W  
koud wit : 6000K - 440lm - CRI >75  
4 x LED (inclusief) 0.96W  
warm wit : 2700K - 456lm - CRI >93  
lichtbundel : 10° - 25° - 40°

### Source lumineuse

4 x power LED (inclus) 1.2W  
blanc froid : 6000K - 440lm - CRI >75  
4 x LED (inclus) 0.96W  
blanc chaud : 2700K - 456lm - CRI >93  
rayon de lumière : 10° - 25° - 40°

### Connection

230V - driver included (not dimmable)  
230V - driver included (IGBT dimmable)

### Aansluiting

230V - voeding inclusief (niet dimbaar)  
230V - voeding inclusief (IGBT dimbaar)

### Connexion

230V - convertisseur inclus (non-dimmable)  
230V - convertisseur inclus (IGBT dimmable)

### Specifications

indoor  
ceiling mounting  
class I  
IP40

### Specificaties

binnen  
plafondmontage  
klasse I  
IP40

### Spécifications

intérieur  
plafonnier  
classe I  
IP40