




R51 UP LED



Material

aluminium

Materiaal

aluminium

Matériau

aluminium



Finish

black - grey - white
interior : black - white
ring : black - grey - white
lens : PMMA

Afwerking

zwart - grijs - wit
interieur : zwart - wit
ring : zwart - grijs - wit
lens : PMMA

Finition

noir - gris - blanc
intérieur : noir - blanc
anneau : noir - gris - blanc
lentille : PMMA

Lightsource

4 x power LED (included) 1.2W
cold white : 6000K - 440lm - CRI >75
4 x LED (included) 0.96W
warm white : 2700K - 456lm - CRI >93
beam : 10° - 25° - 40°

Lichtbron

4 x power LED (inclusief) 1.2W
koud wit : 6000K - 440lm - CRI >75
4 x LED (inclusief) 0.96W
warm wit : 2700K - 456lm - CRI >93
lichtbundel : 10° - 25° - 40°

Source lumineuse

4 x power LED (inclus) 1.2W
blanc froid : 6000K - 440lm - CRI >75
4 x LED (inclus) 0.96W
blanc chaud : 2700K - 456lm - CRI >93
rayon de lumière : 10° - 25° - 40°

Connection

230V - driver included (TRIAC dimmable)
230V - driver included (1-10V / PUSH)

Aansluiting

230V - voeding inclusief (TRIAC dimbaar)
230V - voeding inclusief (1-10V / PUSH)

Connexion

230V - convertisseur inclus (TRIAC dimmable)
230V - convertisseur inclus (1-10V / PUSH)

Specifications

indoor
ceiling mounting
class I
IP40

Specificaties

binnen
plafondmontage
klasse I
IP40

Spécifications

intérieur
plafonnier
classe I
IP40