



## Super Flat Suspension 120x30 Down No Dimmable

#### 09.5040.14B - Black

General lighting LED luminaire to be suspended from ceiling. Power supply included.

#### Main specifications

Number of neads	I
Lamp category	LED
Power (W)	56W
CCT (K)	3000K
CRI	90


Net lumen (lm) Mountings Environment

4441 Suspension Indoor dry location

### Optical

Lighting type
LED type
Light distribution
Optical type
Beam angle (°)
Beam angle C90-270 (°)

Direct Top LED Symmetric Wide flood 105 96



Luminous flux luminaire


Bean	n Angle:	105
h(m)	E(lx)	D(m)
1	1529	2.62
2	382	5.25
3	170	7.87

96 10.49 61 13.12

# 4441 lm (EXTREME CUT OFF)

3000	_4
-	_
	30 20

1200



	lectrical
-	loctrica l
_	<del>-</del> Cuicai

Frequency (Hz)	50/60	Emergency	Without
Voltage (V)	35.00	Insulation class	1
Dimmable	No		
Driver	Integrated		
Driver type	Non Dimmable		

#### Physical

Color	Black
Orientation	Fixed
Weight (kg)	4.20

#### Note

Total consumption of the system: 56W. Light source: max. 6964 lm. Luminous efficiency of luminaire: max. 138 lm/W.