



PIRRO SYSTEM

CEILING SURFACE



165




257




CHOOSE YOUR BASE

1.0 ceiling base
ceiling base for 2 insets
aluminium powder coated




	CODE
	90052072
	90052074
	90052073

2.0 ceiling base
ceiling base for 3 insets
aluminium powder coated



	CODE
	90052075
	90052077
	90052076



2.0 OPAL

LED PCB 7W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium powder coated
opal PMMA cover

IP20 95° SDCM3 L80|50K 0.30kg

	CODE
	151284E
	151284J
	151284K
	151284B

LIGHT COLOUR	LUMEN CRI	CODE
2700K	240 >90	3
3000K	260 >90	5




2.0 SPOT

2x LED COB 5W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium powder coated
PC lens and reflector

IP20 32° SDCM2 L80|50K 0.30kg

	CODE
	151264E
	151264J
	151264K
	151264B

LIGHT COLOUR	LUMEN CRI	CODE
2700K	2x380 >90	3
3000K	2x405 >90	5




4.0 OPAL

LED PCB 12W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium powder coated
opal PMMA cover

IP20 95° SDCM3 L80|50K 0.52kg

	CODE
	151484E
	151484J
	151484K
	151484B

LIGHT COLOUR	LUMEN CRI	CODE
2700K	550 >90	3
3000K	580 >90	5



4.0 SPOT

4x LED COB 5W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium powder coated
PC lens and reflector

IP20 32° SDCM2 L80|50K 0.48kg

	CODE
	151464E
	151464J
	151464K
	151464B

LIGHT COLOUR	LUMEN CRI	CODE
2700K	4x380 >90	3
3000K	4x405 >90	5