




SIRRO

CEILING SURFACE




2.0 LED

2x LED COB 10W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium powder coated

IP20 0°-35°|355° 36° SDCM2 L80|50K 1.57kg

CODE	
	189264W
	189264E
	189264B

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	2x715	>90	3
3000K	2x775	>90	5
2000-3000K	2x560	>95	9



2.0 PAR16

2x PAR16 max. 12W | GU10
100-240VAC | 50-60Hz
aluminium powder coated

IP20 0°-35°|355° 1.51kg


CODE	
	139220W0
	139220E0
	139220B0

OPTIONAL

PAR16 6.5W | GU10 | phase-cut dim

CODE	
 2700K 460lm	901228W3
 2700K 437lm	901228B3
 3000K 500lm	901228W5
 3000K 457lm	901228B5

more lamps and specs on page 731



3.0 PAR16

3x PAR16 max. 12W | GU10
100-240VAC | 50-60Hz
aluminium powder coated

IP20 0°-35°|355° 1.51kg

CODE	
	139320W0
	139320E0
	139320B0

OPTIONAL

PAR16 6.5W | GU10 | phase-cut dim

CODE	
 2700K 460lm	901228W3
 2700K 437lm	901228B3
 3000K 500lm	901228W5
 3000K 457lm	901228B5

more lamps and specs on page 731