





SARA on base

CEILING SURFACE



p. 379 p. 551



1.0 PAR16

PAR16 max. 12W | GU10
100-240VAC | aluminium
powder coated

0.23kg IP20

90°

	CODE
	157220W0
	157220G0
	157220B0
	157220K0

OPTIONAL

PAR16 LED GU10 7W | phase-cut dim

	CODE
2700K white	901228W2
2700K black	901228B3
3000K white	901228W4
3000K black	901228B5

more lamps and specs on page 729

1.1 PAR16

PAR16 max. 12W | GU10
100-240VAC | aluminium
powder coated

0.32kg IP20

90° 330°

	CODE
	157420W0
	157420B0
	157420K0

OPTIONAL

PAR16 LED GU10 7W | phase-cut dim

	CODE
2700K white	901228W2
2700K black	901228B3
3000K white	901228W4
3000K black	901228B5

more lamps and specs on page 729

3.0 PAR16

3x PAR16 max. 12W | GU10
100-240VAC | aluminium
powder coated

0.74kg IP20

90° 330°

	CODE
	157520W0
	157520B0
	157520K0

OPTIONAL

PAR16 LED GU10 7W | phase-cut dim

	CODE
2700K white	901228W2
2700K black	901228B3
3000K white	901228W4
3000K black	901228B5

more lamps and specs on page 729

