



1.0 LED

LED 6W | 220-240VAC | 50-60Hz
COB 3-step | phase-cut dim
aluminium powder coated

0.43kg IP20 39°

90°

	CODE
	144264W
	144264B

LIGHT COLOUR	LUMEN CRI	CODE
2700K	415 >80	2
3000K	430 >80	4
1800-3000K	350 >80	9

OPTIONAL

dimmer

phase-cut +
bluetooth

more dimmers and specs on page 728

2.0 LED

LED 12W | 220-240VAC | 50-60Hz
COB 3-step | phase-cut dim
aluminium powder coated

0.44kg IP20 39°

90°

	CODE
	144464W
	144464B

LIGHT COLOUR	LUMEN CRI	CODE
2700K 32°	711 >80	2
3000K 32°	790 >80	4
1800-3000K 58°	790 >80	9

OPTIONAL

dimmer

phase-cut +
bluetooth

more dimmers and specs on page 728

1.0 PAR16

PAR16 max. 12W | GU10
100-240VAC | 50-60Hz
aluminium powder coated

0.43kg IP20 39°

90°

	CODE
	144220W0
	144220B0

OPTIONAL

PAR16 LED GU10 7W | phase-cut dim

	CODE
2700K white	901228W2
2700K black	901228B3
3000K white	901228W4
3000K black	901228B5

more lamps and specs on page 729

SQUBE on base

CEILING SURFACE



p. 381

p. 391



PAR16



LED

for LED version inner
ring is always black