

Surface-mounted canopy 0-40° for system pendant luminaires for indoor use

Project · Reference number


Date

Product data sheet

Application

Installation component – Surface-mounted canopy (type B) – for interior use.
For the electrical installation and mounting of a BEGA system pendant luminaire on straight or sloped ceilings with an inclination of 0-40°.

Product description

Metal hanger and mounting plate
2 mounting holes \varnothing 4.3 mm
Distance apart 18 x 45 mm
Canopy made of synthetic material, finish velvet white
Synthetic 2-piece line connector (clamp part with screw cap) for braided coaxial cables
With internal pressure spring and contact wire
For connecting a cable pendant
2 x 0,5² or 2 x 0,5², colour: white
Protection class IP 20
LED power supply unit in the canopy
Primary: 220-240 V \sim 0/50-60 Hz
DC 176-275 V
DALI controllable
Secondary: 700 mA DC · 7 - 26 W
Safety class I
05 – Safety mark
CE – Conformity mark
Weight: 0.3 kg

Inrush current

Inrush current: 5 A / 50 μ s
Maximum number of luminaires of this type per miniature circuit breaker:
B 10A: 31 luminaires
B 16A: 50 luminaires
C 10A: 52 luminaires
C 16A: 80 luminaires

