

Recessed canopy for system pendant luminaires for indoor use

Project · Reference number

Date

Product data sheet

Application

Installation component – Recessed canopy (type C) for interior use.
For the electrical installation and mounting of a BEGA system pendant luminaire on straight or sloped ceilings with an inclination of 0-40°.

Product description

Recessed ceiling installation frame and metal hanger

Recessed opening \varnothing 76 mm

Recessed depth required 50 mm

The recessed ceiling installation frame is attached via 2 adjustable claws, arranged in a wedge formation.

Synthetic canopy cover, exterior velvet white

Synthetic 2-piece line connector (clamp part with screw cap) for braided coaxial cables

With internal pressure spring and contact wire

For connecting a cable pendant

2 x 0,5² or 2 x 0,5², colour: white

Protection class IP 20


External LED power supply unit

Primary: 220-240 V \sim 0/50-60 Hz


DC 176-280 V

DALI controllable

Secondary: 500 mA DC · max. 20 W

Safety class II 

05 – Safety mark

 – Conformity mark

Weight: 0.25 kg

Inrush current

Inrush current: 5 A / 50 μ s

Maximum number of luminaires of this type per miniature circuit breaker:

B 10A: 31 luminaires

B 16A: 50 luminaires

C 10A: 52 luminaires

C 16A: 85 luminaires

