

Recessed canopy for system pendant luminaires for indoor use

Project · Reference number

Date

Product data sheet

Application

Installation component – Recessed canopy (type C) for interior use.
For the electrical installation and mounting of a BEGA system pendant luminaire on straight or sloped ceilings with an inclination of 0-40°.

Product description

Recessed ceiling installation frame and metal hanger
Recessed opening $\varnothing$ 76 mm
Recessed depth required 60 mm
The recessed ceiling installation frame is attached via 2 adjustable claws, arranged in a wedge formation.
Synthetic canopy cover, exterior velvet white
Synthetic 2-piece line connector (clamp part with screw cap) for braided coaxial cables
With internal pressure spring and contact wire
For connecting a cable pendant
2 x 0,5" or 2 x 0,5", colour: white
Protection class IP 20
External LED power supply unit
Primary: 220-240 V $\sim$ 0/50-60 Hz
DC 176-275 V
DALI controllable
Secondary: 700 mA DC · 7 - 26 W
Safety class II 
05 – Safety mark
CE – Conformity mark
Weight: 0.25 kg

Inrush current

Inrush current: 5 A / 50 μ s
Maximum number of luminaires of this type per miniature circuit breaker:
B10A: 31 luminaires
B16A: 50 luminaires
C10A: 52 luminaires
C16A: 85 luminaires

