

Date \_\_\_\_\_

\_\_\_\_\_

Name \_\_\_\_\_

\_\_\_\_\_

Client \_\_\_\_\_

\_\_\_\_\_

Project name \_\_\_\_\_

\_\_\_\_\_

Quote# \_\_\_\_\_

\_\_\_\_\_



Type/Quantity \_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

## LOGIC MINI WR 304 30 12

[Weblink](#)



Opening formaat:	⌀ 55 mm
Inbouwdiepte:	50 mm
Dikte montageoppervlak:	min.12
Beschikbare kleuren:	ALU GRIJS (304 30 12 A) WIT (304 30 12 W)

1 x LED 0,6W / 3000K / 40lm  
EXCL.LED POWER SUPPLY 24V-DC  
Not Dimmable

LED Technics:	Lichtbron: 45 lm // 67 lm/W Luminaire: 4 lm // 2 W // 2 lm/W
---------------	---

24V-DC

Klasse:	III
Gewicht:	0.2 KG
Protection level:	IP54
Minimumafstand:	n.v.t.

Opties: CONCRETE BOX 188

Benodigheden: LED POWER SUPPLY 24V-DC


Voor gedetailleerde installatie-instructies, raadpleeg de handleiding: [304\\_30\\_12\\_HAND.pdf](#)

**LOGIC MINI WR**  
304 30 12

**Related references**


**LED VOEDINGEN**

[Weblink / Specificatieblad](#)



LED POWER SUPPLY 24V-DC / 150W  
300 89 24 150  
100-240V / 0/50-60Hz  
Aantal toestellen: 225

[Weblink / Specificatieblad](#)




LED POWER SUPPLY 24V-DC / 24W  
21012 0160  
220-240V / 50-60Hz  
Aantal toestellen: 36

**Related references**

**BETON DOOS**

[Weblink / Specificatieblad](#)



CONCRETE BOX 188  
270 11 188

LOGIC MINI W R  
304 30 12

Gerelateerde project foto van product familie:

