BEGA 55 018

Plug & Play Garden luminaire



Project · Reference number

Date

# Product data sheet

#### **Application**

BEGA Plug & Play

Portable garden luminaire with earthspike, connecting cable and 48 V plug.

Luminaire with opal glass for a soft and uniform light distribution.

#### **Product description**

Luminaire with earthspike made of glass-fibre reinforced polyamide synthetic

Opal glass with screw neck

Silicone gasket

5 m mains supply cable with 48 V plug

Safety class III 🕸

Protection class IP 65

Dust-tight and protection against water jets

Impact strength IK06

Protection against mechanical

impacts < 1 joule

C ∈ – Conformity mark

Weight: 1.0 kg

# Lighting technology


Luminaire data for the DIALux lighting design program for outdoor lighting, street lighting and indoor lighting, as well as luminaire data in EULUMDAT and IES format are available on the BEGA website at www.bega.com.

## Lamp

### 55 018 K3

Module designation	LED-0684/830
Colour temperature	3000 K
Colour rendering index	CRI > 80
Module luminous flux	295 lm
Luminaire luminous flux	236 lm
Luminaire luminous efficiency	98,3 lm/W





### Service life · Ambient temperature

Rated temperature  $t_a = 25$  °C

LED psu: > 50,000 h

LED module: > 200,000h (L80B50)

100,000h (L90B50)

Ambient temperature max. t<sub>a</sub>= 60 °C (100 %)

LED psu: 50,000h

LED module: 160,000h (L80 B50)

# Accessories

**13566** Smart Tower with connecting cable

and mains plug

**13567** Smart Tower with connecting cable

and free cable end

13568 Smart Extender

Distributor with 5 m cable and 48 V plug, switchable and dimmable via

Zigbee Conrol module

10596 Extension cable 5 m

**10 597** Extension cable 10 m

10 526 Remote control ONE13 569 Remote control PRO

**70 588** Gateway

for controlling your lighting system by app BEGA Gateway from a smartphone or tablet

For the accessories a separate instructions for use can be provided upon request.

# Light distribution

