





SOLI - FORM 60 DOWN-UP 83067 MDL B-MMAT 27136 8320 B-MMAT

AVAILABLE IN
BLACK-BLACK 27136 8320 B-B
BLACK-GOLD MATT 27136 8320 B-MMAT
WHITE-BLACK 27136 8320 W-B
WHITE-WHITE 27136 8320 W-W



 [View on website](#)

General info

LOCATION	interior
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.5
ADJUSTABILITY	non adjustable
INFORMATION	INCL.24 x REFLECTOR FL-67° EXCL.LED POWER SUPPLY 48V-DC MELANOPIC LIGHT TECHNOLOGY

Electrical info

ELECTRICAL	48V-DC
CLASS	III
DIM TYPE	MDL = 1-10V or DALI or push button
ENERGY CLASS	D

Lightsource info

Lightsource Name	LED
Lightsource	DOWN: LED cluster 6,6W / CRI>80 / 3000K / 1126lm UP: LED cluster 6,6W / CRI>80 / 3000K / 1126lm
TM-30 Values	Rf: 85 / Rg: 94
SDCM	SDCM3
Riskgroup	RG2
LM80	L90 > 60000
LED Technics (light source)	DOWN: 1126lm // 6,6W // 171lm/W UP: 1126lm // 6,6W // 171lm/W
LED Technics (luminaire)	DOWN: 957lm // 8W // 126lm/W UP: 754lm // 8W // 99lm/W

Requirements

LED POWER SUPPLY 48V-DC

Options

DIMMABLE MODULATOR

SOLI - FORM 60 DOWN-UP 83067 MDL B-MMAT


27136 8320 B-MMAT

For detailed installation instructions, please consult the manual: [27136_XXX0_HAND.pdf](#)

FINISH YOUR SPECIFICATION


SMART 48

#



300 90 011 SMART 48 MODULATOR DIM9

12




300 90 012 SMART 48 MODULATOR WD

12


LED power supplies

#




300 89 48 100 LED POWER SUPPLY 48V-DC / 100W DIN

6




300 89 48 240 LED POWER SUPPLY 48V-DC / 240W DIN

15



21012 0230 LED POWER SUPPLY 48V-DC / 100W

6



21012 0240 LED POWER SUPPLY 48V-DC / 200W

12


SOLI - FORM 60 DOWN-UP 83067 MDL B-MMAT

27136 8320 B-MMAT


COMPATIBLE COMPOSABLES

SOLISCAPE profile

Available Colours



27111 0020 SOLI - PROFILE 2m



27111 0030 SOLI - PROFILE 3m



Notes: