

PUNTO Ø 250/320/420 mm Mounted lamps



Product description

Art. No.: 4051.250.27.8
 Product name: PUNTO mounted lamp
 Housing colour: grey RAL 9006
 Material: Diecast aluminium
 Equipment: Can be mounted on the ceiling or wall with plug connection
 Dimensions (mm): Ø250 x 70
 Optics/light technology: acrylic glass diffuser fine mat
 Weight: 2.06
 Protection level: IP 34
 Protection class: I
 Control gear: PS 230 V/50 Hz
 Lighting control: on/off


Light specification/technical data

Lamp: LED
 System power: 10
 Light flux: 1170
 Luminous efficiency (lm/W): 117
 Colour temperature (K): 2700
 Colour rendering index: >90
 Unified glare rating: 22
 Light distribution: Direct beam
 Lifetime: 100'000h L80 B10 (Ta 25° C)
 Energy efficiency: D
 Colour consistency (MacAdam): 3

Specification text/Description: Article: 4051.250.27.8; Article name: PUNTO mounted lamp; Description: With very high luminous efficiency and low glare, PUNTO provides perfect uniformity of light and offers a wide range of applications. The diffuser, sealed against dust and moisture, allows for long-term use in indoor and sheltered outdoor areas. The patented quick mounting system means easy mounting on the walls and ceilings.; Color: grey RAL 9006; Optics: acrylic glass diffuser fine mat; Light control: on/off; Watt: 10W; Kelvin: 2700K; Lumen: 1170lm; Materialisation: aluminium; Control gear: control gear 230 V/50 Hz; CRI: >90; Protection class: I; Protection level: IP 34; UGR: 22; Weight (incl. packaging): 2,06kg; ø: 250mm; Dimension (mm): Ø250 x 70mm

Drawings

Art. No.: 4051.250.27.8



Light distribution

