

PUNTO Ø 250/320/420 mm Mounted lamps



Product description

Art. No.: 4051.420.30.8 DIG
Product name: PUNTO mounted lamp
Housing colour: grey RAL 9006
Material: Diecast aluminium
Equipment: Can be mounted on the ceiling or wall with plug connection
Dimensions (mm): Ø420 x 80
Optics/light technology: acrylic glass diffuser fine mat
Weight: 4.98
Protection level: IP 34
Protection class: I
Control gear: PS 230 V/50 Hz
Lighting control: DALI/TouchDIM


Light specification/technical data

Lamp: LED
System power: 21
Light flux: 2650
Luminous efficiency (lm/W): 126
Colour temperature (K): 3000
Colour rendering index: >90
Unified glare rating: 22
Light distribution: Direct beam
Lifetime: 100'000h L80 B10 (Ta 25° C)
Energy efficiency: D
Colour consistency (MacAdam): 3

Specification text/Description: Article: 4051.420.30.8 DIG; Article name: PUNTO mounted lamp; Description: With very high luminous efficiency and low glare, PUNTO provides perfect uniformity of light and offers a wide range of applications. The diffuser, sealed against dust and moisture, allows for long-term use in indoor and sheltered outdoor areas. The patented quick mounting system means easy mounting on the walls and ceilings.; Color: grey RAL 9006; Optics: acrylic glass diffuser fine mat; Light control: DALI/TouchDIM; Watt: 21W; Kelvin: 3000K; Lumen: 2650lm; Materialisation: aluminium; Control gear: control gear 230 V/50 Hz; CRI: >90; Protection class: I; Protection level: IP 34; UGR: 22; Weight (incl. packaging): 4,98kg; ø: 420mm; Dimension (mm): Ø420 x 80mm

Drawings

Art. No.: 4051.420.30.8 DIG



Light distribution

