

ARVA with acrylic glass diffuser fine matt finish Pendant lamps



Product description

Art. No.: 4110.420.27.3

Product name: ARVA pendant lamp

Housing colour: white RAL 9003

Material: Diecast aluminium

Equipment: For mounting on the ceiling, cable diam \varnothing 7 mm with steel cord, length 2500 mm, order canopy with control gear or cavity adapter and control gear separately

Dimensions (mm): \varnothing 440 x 50

Optics/light technology: acrylic glass diffuser fine mat

Function: white cable 2500 mm

Weight: 6.60

Protection level: IP 40

Protection class: I

Control gear: PS 230 V/50 Hz, constant current 700 mA (for \varnothing 270 mm), 800 mA (for \varnothing 440 mm)

Light specification/technical data

Lamp: LED

System power: 30

Light flux: 3450

Luminous efficiency (lm/W): 115

Colour temperature (K): 2700

Colour rendering index: >90

Unified glare rating: 25

Light distribution: Direct/indirect beam

Lifetime: 100'000h L80 B10 (Ta 25° C)

Energy efficiency: C (according to current EU labelling requirements, corresponds to A+ - A++), contains built-in LED


lamps, lamps replaceable by the manufacturer

Colour consistency (MacAdam): 3

Specification text/Description: Article: 4110.420.27.3; Article name: ARVA pendant lamp; Description: The robust aluminium housing with sealed diffuser makes the luminaire particularly durable and protects it from dust and insects.; Color: white RAL 9003; Optics: acrylic glass diffuser fine mat; Watt: 30W; Kelvin: 2700K; Lumen: 3450lm; Materialisation: aluminium; white cable 2500 mm; Control gear: constant current 800mA; CRI: >90; Protection class: I; Protection level: IP 40; UGR: 25; Weight (incl. packaging): 6,6kg; \varnothing : 440mm; Dimension (mm): \varnothing 440 x 50mm

Drawings

Art. No.: 4110.420.27.3



Light distribution

