# RIBAG

## ARVA with acrylic glass diffuser fine matt finish Mounted lamps



#### **Product description**

Art. No.: 4120.120.27.2 Product name: ARVA mounted lamp/ext. control gear Housing colour: black RAL 9005 Material: Diecast aluminium Equipment: Can be mounted on the ceiling or wall Dimensions (mm): Ø140 x 43 Optics/light technology: acrylic glass diffuser fine mat Weight: 0.84 Protection level: IP 54 Protection class: I Control gear: PS 230 V/50 Hz, constant current 250 mA (order separately)


### Light specification/technical data

Lamp: LED System power: 4 Light flux: 490 Luminous efficiency (lm/W): 123 Colour temperature (K): 2700 Colour rendering index: >90 Unified glare rating: 25 Light distribution: Direct beam Lifetime: 100'000h L80 B10 (Ta 25° C) Energy efficiency: C (according to current EU labelling requirements, corresponds to A+ - A++), contains built-in LED lamps, lamps replaceable by the manufacturer Colour consistency (MacAdam): 3

**Specification text/Description:** Article: 4120.120.27.2; Article name: ARVA mounted lamp/ext. control gear; Description: The robust aluminium housing with sealed diffuser makes the luminaire particularly durable and protects it from dust and insects.; Color: black RAL 9005; Optics: acrylic glass diffuser fine mat; Watt: 4W; Kelvin: 2700K; Lumen: 490lm; Materialisation: aluminium; Control gear: constant current 250mA; CRI: >90; Protection class: I; Protection level: IP 54; UGR: 25; Weight (incl. packaging): 0,84kg; ø: 140mm; Dimension (mm): Ø140 x 43mm

#### Drawings

Art. No.: 4120.120.27.2



RIBAG Licht AG Kanalstrasse 18 5745 Safenwil / Schweiz info@ribag.com www.ribag.com T +41 62 737 90 10 The technical data refer to rated values at an ambient temperature of 25°C and are guide values with a tolerance of +/- 10%. Subject to change without notice. No liability is accepted for printing errors. Prices are subject to change without notice. © RIBAG Licht AG 12.3.2022

Light distribution