

Technical data

Rated voltage	230V AC
Input voltage range	230 - 250 V AC
Driver output	-
Alimentation output	-
Class	1
IP	66
IK	-
Diffuser	Opal PMMA
Bulb cover	-
Source	E27
Real light output	- lm
Energy class	A++ / E
SDCM	-
Optic	-
Dimmable	-
Ta	-
Led lifetime	-
Ambient temperature range	-10 ~50°C
UGR	-
ULR	-
THDI	-
Fixing kit	Yes
With sensor	No
With IP55 socket	No

[Download the installation manual](#)

Materials and finishes

Material	aluminium
Colour	Jet black - 000 - RAL 9005

Logistic data

Product dimensions	H.4411 L.1703 P.509
Net weight	0.000 Kg
Gross weight	0.000 Kg
Package dimensions 1	H.410 L.410 P.1180
Package dimensions 1	H.140 L.140 P.3350
Package dimensions 3	H.600 L.520 P.940
Package dimensions 4	H.600 L.520 P.940
Package dimensions 5	H.650 L.510 P.120
Package dimensions 6	H.650 L.510 P.120

Certifications and warranties

CE	Yes
UL	No
EAC	Yes
RoHS	Yes
ENEC	No
Anti-corrosion	25 years
Technical	5 years
Electronics	5 years