


Fort Knox Wall LED Dali Version

09.2110.05CDA - Polished Aluminium

Designed by Philippe Starck

Wall-mounted LED luminaire for indirect lighting. Power source incorporated into luminaire's body.




Main specifications

Mounting	Wall surface	Dimmable	Yes
Environment	Indoor dry location	Autoprotected Lamp	No
LED type	Power LED	Number of heads	1
Lamp category	LED	Source Power (W)	35W
Ilcos	No	System Flux (lm)	3036

Optical

Lighting Type	Indirect
Lighting distribution	Asymmetric
CCT (K)	3000K
CRI>	90
Cold Beam Lighting	No
Beam angle C0-180 (°)	29
Beam angle C90-270 (°)	86
Extreme Cut off	No



Beam Angle:	30°		
h(m)	E(lx)	D(m)	
1	52	18.90	
2	12	37.79	
3	6	56.69	
4	3	75.58	
5	3	94.48	

Luminous flux luminaire
3036 lm

Electrical

Insulation class	I	Dimmable type	Dimmable DALI
Frequency (Hz)	50/60	Emergency Type	No
Main Voltage (Vac)	220		
Driver	Integrated		
Dimmable	Yes		

Physical

Colour	Polished Aluminium	IP	20
Trim	No	IP external	20
Orientations	Fixed		
Length (mm)	150		
Net weight (kg)	1.4		

