

**Materials and colours**

opaline glass cylinder with brass black varnished stem

NOTE: the stems of the Syphasera collection are made of brass protected for outdoor with black coloured varnish. In case of installation into water, we recommend a version available on request designed for this kind of projects and requests.

Light source


LED bulb G4 12V DC 1x1,5W / energy class A+ / lumen 150 / K 2700 / CRI 85 / protection grade IP65

NOTE: IP specifics - lamp holder IP65 (not protected against immersion); wires and connectors IP68; drivers IP67; IP average rate of the lamp 44.

Power supply

12V DC transformer not included

Dimensions



cylinder with holder
Ø 1,5 x H 21 cm
H tot. 65 cm (cable 255 cm)
H tot. 80 cm (cable 240 cm)
H tot. 110 cm (cable 210 cm)
H tot. 140 cm (cable 180 cm)

Order code

SYS65 H 65 cm
SYS80 H 80 cm
SYS110 H 110
cm
SYS140 H 140
cm

Accessories for gel box system

ED6 driver 10W 12V DC 220-240V IP67 not dimmable (max 6 lamps)
MB1 mini gel box IP68 (max 2 connections, connector included)
MB2 mini gel box IP68 (max 6 connections, connector included)
KP1 extension kit 5 mt with mini gel box IP68 (max 1 lamp)

Accessories for quick connectors system

ED6CR driver 10W 12V DC 220-240V IP67 not dimmable with quick connectors (max 6 lamps)
CRM multiple quick connector IP68 - 1 IN & 5 OUT (max 5 connections)
CRS single quick connector IN IP68
KP2 extension kit 5 mt with quick connectors IP68 (max 1 lamp)