



WEVER & DUCRÉ  
LIGHTING

# DEEP ADJUST 1.0 LED

184361M5

Project

Type

Notities

Kwantiteit

Datum

## ALGEMEEN

Plafond

Ingebouwd

Champagne

IP20

Interieur

575<sup>a</sup> tot 775<sup>b</sup> lm

## LED

3000 K

## FYSISCH

Diameter 94 mm

Height 85 mm

0,23 kg

draadveren

Tilt max 35°

Rotation 355°

## ELEKTRISCH

excl. voeding

17 V

LED inset 6<sup>a</sup> tot 9<sup>b</sup> W

350<sup>a</sup> tot 500<sup>b</sup> mA

Klasse 3

Veiligheidsafstand 0,3 m

## CUTOUT

Diameter 86-89 mm


Min. ceiling thickness 4 mm

Max. ceiling thickness 23 mm

Recessed depth 90 mm

<sup>a</sup> 350mA

<sup>b</sup> 500mA





WEVER & DUCRÉ  
LIGHTING

# DEEP ADJUST 1.0 LED

184361M5

## ELEKTRISCH

### Driver

TYPE	L · W · H (MM)	ORDERCODE
10W   500mA   11-20V	100-43-23	9 0 2 1 4 4 0 5
10W   500mA   3-20V	102-49-29	9 0 2 2 4 4 0 2
17W   350mA   10-49V	108-52-22	9 0 2 4 3 6 0 1
20W   500mA   9-45V	116-40.5-22	9 0 2 4 4 6 0 4

## ANDERE

### Metalen veerklem

TYPE	(MM)	ORDERCODE
MR16   LED   PAR16   max. 12W	59	9 0 0 1 9 7 0 0



059

### Veerklem

TYPE	KLEUR	(MM)	ORDERCODE
MR16   LED   PAR16   max. 12W	Zwart	59	9 0 0 1 9 8 B 0
MR16   LED   PAR16   max. 12W	Goud	59	9 0 0 1 9 8 G 0
MR16   LED   PAR16   max. 12W	Brons	59	9 0 0 1 9 8 Q 0
MR16   LED   PAR16   max. 12W	Zilver	59	9 0 0 1 9 8 S 0
MR16   LED   PAR16   max. 12W	Wit	59	9 0 0 1 9 8 W 0