



WEVER & DUCRÉ
LIGHTING

DEEP ADJUST 1.0 PAR16

112320B0C

Project

Type

Notities

Kwantiteit

Datum

ALGEMEEN

Plafond

Ingebouwd

Gitzwart

IP20

Interieur

445 lm

RAL 9005^a

LED

Lamp PAR16

PAR16

Socket GU10

max. 12 W

CRI 90

OPTISCH

Wide Flood

Beam angle 48°

FYSISCH

Diameter 94 mm

Height 102 mm

0.21 kg

bladveren

Tilt min 35°

Tilt max 35°

Rotation 355°

ELEKTRISCH

100 - 240 V

Totaal aangesloten vermogen 6.5 W

LED inset 6.5 W

PC2

Safety distance 0.3 m




CUTOUT

Diameter 86-89 mm


Min. ceiling thickness 6 mm

Recessed depth 105 mm

^a RAL-kleuren kunnen lichtjes afwijken
omwille van productieomstandigheden.



LICHTVERDELING





WEVER & DUCRÉ
LIGHTING

DEEP ADJUST 1.0 PAR16

112320B0C

KEGELDIAGRAM

wide flood 48°

h (m)	EO° (lx)	ø (m)
1	657	0.89
2	164	1.78
3	73	2.66
4	41	3.55
5	26	4.44

ANDERE

Metal spring clip

TYPE	(MM)	ORDERCODE
MR16 LED PAR16 max. 12W	59	9 0 0 1 9 7 0 0



ø59

Veerklem

TYPE	KLEUR	(MM)	ORDERCODE
MR16 LED PAR16 max. 12W	Zwart	59	9 0 0 1 9 8 B 0
MR16 LED PAR16 max. 12W	Goud	59	9 0 0 1 9 8 G 0
MR16 LED PAR16 max. 12W	Brons	59	9 0 0 1 9 8 Q 0
MR16 LED PAR16 max. 12W	Zilver	59	9 0 0 1 9 8 S 0
MR16 LED PAR16 max. 12W	Wit	59	9 0 0 1 9 8 W 0

LAMPS

PAR16 LED lamp

TYPE	KLEUR	Ø · H (MM)	ORDERCODE
2700K >90 CRI GU10	Zwart	ø50 · 58	9 0 1 2 2 8 B 3
3000K >90 CRI GU10	Zwart	ø50 · 58	9 0 1 2 2 8 B 5
2700K >90 CRI GU10	Wit	ø50 · 58	9 0 1 2 2 8 W 3
3000K >90 CRI GU10	Wit	ø50 · 58	9 0 1 2 2 8 W 5
2700K >80 CRI GU10	Zilver	ø50 · 52	9 0 5 2 2 7 S 2
3000K >80 CRI GU10	Zilver	ø50 · 52	9 0 5 2 2 7 S 4