



DEEP ADJUST trimless

Ceiling recessed



1.0 LED

LED COB 6,9W | 350/500mA | 17V
aluminium

IP20 0°-35°/355° A-34° SDCM2 L80/55K 0.23kg

CODE
184861W_
184861G_
184861B_

LIGHT COLOUR	LUMEN CRI	CODE
2700K	530/715 >90	3
3000K	575/775 >90	5
4000K	620/830 >90	7
2000-3000K	380/560 >90	9

LED module 20 years replaceability

ALWAYS USE


alu plasterkit 105-110 95 12,5, 15, 20, 25

CODE 90017209

driver | 500mA

CODE
10W 90214406
10W dim 90224403
24W DALI 90244701

more options and specs on page 808



1.0 MR16

QR-CBC51 max. 12W | GU5.3 | 12V
aluminium

IP20 0°-35°/355° 0.17kg

CODE
112810W0
112810G0
112810B0

LIGHT COLOUR	LUMEN CRI	CODE
2700K	460lm	901228W3
2700K	437lm	901228B3
3000K	500lm	901228W5
3000K	457lm	901228B5

more options and specs on page 810

ALWAYS USE


alu plasterkit 105-110 95 12,5, 15, 20, 25

CODE 90017209

driver | 12V

CODE
10W 90214406
10W dim 90224403
24W DALI 90244701

more options and specs on page 810



1.0 PAR16

PAR16 max. 12W | GU10
100-240VAC | 50-60Hz
aluminium

IP20 0°-35°/355° 0.21kg

CODE
112820W0
112820G0
112820B0

LIGHT COLOUR	LUMEN CRI	CODE
2700K	460lm	901228W3
2700K	437lm	901228B3
3000K	500lm	901228W5
3000K	457lm	901228B5

more options and specs on page 810

ALWAYS USE

alu plasterkit 105-110 95 12,5, 15, 20, 25

CODE 90017209

OPTIONAL

PAR16 6.5W | GU10 | phase-cut dim

CODE 90017209

driver | 12V

CODE
10W 90214406
10W dim 90224403
24W DALI 90244701

more options and specs on page 810



MORE BEAM ANGLES ONLINE

weverducre.com/more-deep-adjust-trimless