




# DEEPER

Ceiling recessed



## 1.0 LED

LED COB 6/9W | 350/500mA | 17V aluminium

IP20  $\Delta$  34° SDCM2 L80/55K 0.17kg

wire springs  $\varnothing$  76-79  $\perp$  90  $\approx$  4-38

	CODE
	152361W_
	152361S_
	152361G_
	152361Q_
	152361B_

LIGHT COLOUR	LUMEN CRI	CODE
2700K	505/685 >90	3
3000K	550/740 >90	5
2000-3000K	380/560 >90	9


LED module 20 years replaceability

## ALWAYS USE

driver | 500mA

	CODE
10W	90214406
10W dim	90224403
24W DALI	90244701

more options and specs on page 808



## 1.0 MR16

QR-CBC51 max. 12W | GU5.3 | 12V aluminium

IP20 0.11kg

wire springs  $\varnothing$  76-79  $\perp$  100  $\approx$  4-38

	CODE
	152110W0
	152110S0
	152110G0
	152110Q0
	152110B0

LIGHT COLOUR	LUMEN CRI	CODE
2700K	460lm	902228W3
2700K	437lm	901228B3
3000K	500lm	901228W5
3000K	457lm	901228B5


specifications on page 810

## ALWAYS USE

driver | 12V

	CODE
10W dim	90221401
25W dim	90221701

specifications on page 810



## 1.0 PAR16

PAR16 max. 12W | GU10 100-240VAC | 50-60Hz aluminium

IP20 0.15kg

wire springs  $\varnothing$  76-79  $\perp$  120  $\approx$  4-38

	CODE
	152120W0
	152120S0
	152120G0
	152120Q0
	152120B0

LIGHT COLOUR	LUMEN CRI	CODE
2700K	460lm	901228W3
2700K	437lm	901228B3
3000K	500lm	901228W5
3000K	457lm	901228B5

specifications on page 810

## OPTIONAL

PAR16 6.5W | GU10 | phase-cut dim

	CODE
2700K   460lm	901228W3
2700K   437lm	901228B3
3000K   500lm	901228W5
3000K   457lm	901228B5



BLADE SPRING VERSIONS AND MORE BEAM ANGLES ONLINE

[weverducre.com/more-deeper](http://weverducre.com/more-deeper)

