

1.0 TRIMLESS

LED COB 6W | 350mA | 18V
excl. driver
aluminium powder coated or
aluminium powder coated brushed

IP20 0°-90°/360° A30° SDCM2 L80/50K 0.15kg

45-47 60 4-26

CODE	
190851W_	190851BL_
190851B_	

LIGHT COLOUR	LUMEN CRI	CODE
2700K	535 >90	3
3000K	600 >90	5

ALWAYS USE

driver | 350mA | revision opening
required

CODE	
10W dim	90223402
10W DALI	90243401

more options and specs on page 736

1.0

LED COB 6W | 350mA | 18V
excl. driver
aluminium powder coated or
aluminium powder coated brushed

IP20 0°-90°/350° A30° SDCM2 L80/50K 0.16kg

wire springs 45-47 85 4-26

CODE	
190151W_	190151BL_
190151CH_	190151B_

LIGHT COLOUR	LUMEN CRI	CODE
2700K	535 >90	3
3000K	600 >90	5

ALWAYS USE

driver | 350mA

CODE	
10W dim	90223402
10W DALI	90243401

more options and specs on page 736

2.0

2x LED COB 6W | 700mA | 18V
excl. driver
aluminium powder coated

IP20 0°-90°/350° A30° SDCM2 L80/50K 0.27kg

wire springs 105x30 60 4-26

CODE	
190251W_	190251B_



LIGHT COLOUR	LUMEN CRI	CODE
2700K	2x535 >90	3
3000K	2x600 >90	5

ALWAYS USE

driver | 700mA | only 1x needed

CODE	
15W dim	90225502
28W DALI	90245801

more options and specs on page 739



MATCH

TRIMLESS | CEILING RECESSED



As awarded by The Chicago Athenaeum:
Museum of Architecture and Design

