




RINI SNEAK IP44

CEILING RECESSED



1.0 LED

LED COB 6/9W | 350/500mA | 17V
excl. driver
aluminium powder coated

IP44 36° SDCM2 L80I50K 0.18 kg

wire springs 76-79 46 4-25

	CODE
Light grey	154461W
Black	154461B


LIGHT COLOUR	LUMEN	CRI	CODE
2700K	465/625	>90	3
3000K	505/675	>90	5
2000-3000K	335/495	>90	9

ALWAYS USE

driver | 500mA

	CODE
10W	90214405
10W dim	90224402
20W DALI	90244604

more options and specs on page 725



1.0 MR16

QR-CBC51 max. 12W | GU5.3 | 12V
excl. driver
aluminium powder coated

IP44 0.12 kg

wire springs 76-79 55 4-25

	CODE
Light grey	154210W0
Black	154210B0


LIGHT COLOUR	LUMEN	CRI	CODE
2700K	465/625	>90	3
3000K	505/675	>90	5
2000-3000K	335/495	>90	9

ALWAYS USE

driver | 12V

	CODE
10W dim	90221401
25W dim	90221701
70W dim	90221904

specs on page 727



1.0 PAR16

PAR16 max. 12W | GU10
100-240VAC | 50-60Hz
aluminium powder coated

IP44 0.16 kg

wire springs 76-79 80 4-25

	CODE
Light grey	154220W0
Black	154220B0


LIGHT COLOUR	LUMEN	CRI	CODE
2700K	465/625	>90	3
3000K	505/675	>90	5
2000-3000K	335/495	>90	9

OPTIONAL

PAR16 6.5W | GU10 | phase-cut dim

	CODE
2700K 460lm	901228W3
2700K 437lm	901228B3
3000K 500lm	901228W5
3000K 457lm	901228B5

more lamps and specs on page 731



low recessed
depth only for
LED version