



# DEEP ADJUST

Ceiling recessed



## 1.0 LED

LED COB 6/9W | 350/500mA | 17V aluminium

IP20 0°-35°/355° A 34° SDCM2 L80I55K 0.17kg

wire springs 86-89 90 4-23

	CODE
	184361W_
	184361S_
	184361M_
	184361G_
	184361Q_
	184361B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	530/715	>90	3
3000K	575/775	>90	5
4000K	620/830	>90	7
2000-3000K	380/560	>90	9


LED module 20 years replaceability

### ALWAYS USE

driver | 500mA

	CODE
10W	90214406
10W dim	90224403
24W DALI	90244701

more options and specs on page 808



## 1.0 MR16

QR-CBC51 max. 12W | GU5.3 | 12V aluminium

IP20 0°-35°/355° 0.17kg

wire springs 86-89 90 4-23

	CODE
	112310W0
	112310S0
	112310M0
	112310G0
	112310Q0
	112310B0

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	460	>90	3
2700K	437	>90	5
3000K	500	>90	7
3000K	457	>90	9

LED module 20 years replaceability

### ALWAYS USE

driver | 12V

	CODE
10W dim	90221401
25W dim	90221701

specs on page 810



## 1.0 PAR16

PAR16 max. 12W | GU10 100-240VAC | 50-60Hz aluminium

IP20 0°-35°/355° 0.21kg

wire springs 86-89 115 4-23

	CODE
	112320W0
	112320S0
	112320M0
	112320G0
	112320Q0
	112320B0

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	460lm	>90	3
2700K	437lm	>90	5
3000K	500lm	>90	7
3000K	457lm	>90	9

LED module 20 years replaceability

### OPTIONAL

PAR16 6.5W | GU10 | phase-cut dim

	CODE
2700K   460lm	901228W3
2700K   437lm	901228B3
3000K   500lm	901228W5
3000K   457lm	901228B5



BLADE SPRING VERSIONS AND MORE BEAM ANGLES ONLINE

weverducree.com/more-deep-adjust