





## LOGIC 40 R 93015 ANO

13955 9310 ANO

BESCHIKBAAR IN  
ALU GEANODISEERD 13955 9310 ANO



[Bekijk op website](#)



### Algemene info

|                               |                                                                                                                                                                      |
|-------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>LOCATIE</b>                | buiten                                                                                                                                                               |
| <b>INSTALLATIE</b>            | Vloer Inbouw                                                                                                                                                         |
| <b>ZAAGMAAT/OPENING (MM)</b>  | rond - 43                                                                                                                                                            |
| <b>INBOUWDIEPTE (MM)</b>      | 85                                                                                                                                                                   |
| <b>STOF EN WATERDICHTHEID</b> | IP67                                                                                                                                                                 |
| <b>IK</b>                     | IK08                                                                                                                                                                 |
| <b>GEWICHT (KG)</b>           | 0.2                                                                                                                                                                  |
| <b>RICHTBAARHEID</b>          | niet richtbaar                                                                                                                                                       |
| <b>INFO</b>                   | REFLECTOR SP-15°<br>INCL.1 x CABLE H05 RN-F 2 x 1mm <sup>2</sup> 0,5m<br>EXCL.LED POWER SUPPLY 350mA-DC<br>IEC 60598-2-13 : max.150kg 25N/cm <sup>2</sup><br>ESG 6mm |

### Elektrische info

|                       |                                              |
|-----------------------|----------------------------------------------|
| <b>KLASSE</b>         | III                                          |
| <b>DIM TYPE</b>       | afhankelijk van de te kiezen externe voeding |
| <b>ENERGIE KLASSE</b> | F                                            |
| <b>CERTIFICATEN</b>   | CB, ENEC, EPD                                |

### Info lichtbron

|                                 |                                                  |
|---------------------------------|--------------------------------------------------|
| <b>LIGHTSOURCE NAME</b>         | LED                                              |
| <b>LICHTBRON</b>                | LED array 3,9W / CRI>90 (R9: 55) / 3000K / 385lm |
| <b>TM-30-15 WAARDEN</b>         | rf: 92 / Rg: 98                                  |
| <b>SDCM</b>                     | SDCM2                                            |
| <b>RISK-GROEP</b>               | RG2 (threshold 0,6m)                             |
| <b>LM80</b>                     | L90B10 > 41000                                   |
| <b>LED TECHNIEK (LICHTBRON)</b> | 385lm // 3,9W // 98lm/W                          |
| <b>LED TECHNIEK (TOESTEL)</b>   | 186lm // 4,5W // 42lm/W                          |

### Benodigdheden

LED POWER SUPPLY 350mA-DC DIM

## LOGIC 40 R 93015 ANO

13955 9310 ANO

### Opties

---

LOGIC 40 BOX R

CBOX

IP68 CONNECTION KIT

IP68 CONNECTOR 3P

Voor gedetailleerde montage gegevens, consulteer de handleiding: [13955\\_XXX0\\_HAND.pdf](#)


# LOGIC 40 R 93015 ANO

13955 9310 ANO

## VERVOLLEDIG UW SPECIFICATIE

### LED voedingen


#



**300 90 63**

LED POWER SUPPLY MULTI-POWER DIM9


6(6)



**300 90 68**

LED POWER SUPPLY MULTI-POWER DIM5


4(3)



**300 90 69**

LED POWER SUPPLY MULTI-POWER HV DIM9


2->9(10)



**300 90 124**

LED POWER SUPPLY MULTI-POWER DIM7


2->4(3)



**300 90 125**

LED POWER SUPPLY MULTI-POWER MINI DIM5


4(3)



**21012 0010**

LED POWER SUPPLY MULTI POWER


2->3



**21012 0021**

LED POWER SUPPLY MULTI POWER DIM1


4



**21012 0035**

LED POWER SUPPLY MULTI POWER DIM5

4




**21012 005W**

LED POWER SUPPLY MULTI-POWER COMPACT WDL

4


LOGIC 40 R 93015 ANO

13955 9310 ANO




**21012 0258** LED POWER SUPPLY MULTI POWER 200-350 / 10W DIM8

2->2 ☐




**21012 0268** LED POWER SUPPLY MULTI POWER 200-350 / 15W DIM8

3->3 ☐




**21012 0298** LED POWER SUPPLY MULTI POWER 250-900 / 20W DIM8

3 ☐



**21012 0480** LED POWER SUPPLY 350mA-DC / 17W IP68


4(3) ☐



**21032 0295** LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM5

3 ☐



Grond montage dozen



**13910 0010** LOGIC 40 BOX R

☐

Waterdichte doorverbindingen

|                                                                                   |                                      |                          |
|-----------------------------------------------------------------------------------|--------------------------------------|--------------------------|
|   | <b>216 12 00</b> CBOX                | <input type="checkbox"/> |
|   | <b>216 12 01</b> IP68 CONNECTION KIT | <input type="checkbox"/> |
|  | <b>216 12 02</b> IP68 CONNECTOR 3P   | <input type="checkbox"/> |

Notes: