DELTALIGHT®

SUPER-OH! SLIM 120 HP CS SBL DOWN-UP 930 B

20744 9300 B

AVAILABLE IN
BLACK 20744 9300 B
WHITE 20744 9300 W





View on website

General info	
LOCATION	indoor
INSTALLATION	Ceiling Suspended
INGRESS PROTECTION	IP20
WEIGHT (KG)	7.1
ADJUSTABILITY	non adjustable
INFORMATION	INCL.PC SBL DOWN: INCL.LED POWER SUPPLY 2100mA UP: INCL.LED POWER SUPPLY 1050mA INCL.4 x CABLE SUSPENSION SINGLE AUTO. 3m POWER VIA CABLE SUSPENSION CABLING 2 CIRCUITS

Electrical info	
ELECTRICAL	220-240V / 50-60Hz
CLASS	I
POWER SUPPLY INCLUDED	YES
DIM TYPE	non-dimmable
ENERGY CLASS	D
CERTIFICATES	CB, ENEC

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	DOWN: LED cluster 68,8W / CRI>90 (R9: 50) / 3000K / 10512lm UP: LED cluster 33,1W / CRI>90 (R9: 50) / 3000K / 5304lm
SDCM	SDCM3
LM80	L80 > 60000
LED TECHNICS (LIGHT SOURCE)	DOWN: 10512lm // 68,8W // 153lm/W UP: 5304lm // 33,1W // 160lm/W
LED TECHNICS (LUMINAIRE)	DOWN: 7022lm // 79W // 89lm/W UP: 4010lm // 38W // 105lm/W

For detailed installation instructions, please consult the manual: **20744_XXX0_HAND.pdf**

SUPER-OH! SLIM 120 HP CS SBL DOWN-UP 930 B

20744 9300 B

Notes: