



in S . symmetric Design: IP44.de

für unbefestigte Beet- und Grünflächen

for unpaved beds and greens

Lichttechnik:
230V Power LED
2700K + 3000K
L70/50.000 h

Material:
Abdeckring: Edelstahl
Glas: Sicherheitsglas
Gehäuse: Polyamid, Glasfaser verstärkt

light technology:
230V Power LED
2700K + 3000K
L70/50.000 h

material:
cover ring: stainless steel
glass: safety glass
housing: polyamide, fibre glass reinforced

Reflektor: Flood symmetrisch

reflector: flood symmetric

dimmbar

Schutzart:
IP67

dimmable

protection class:
IP67

Installation:
2 m Anschlussleitung (H05RN8-F 3G0,75) mit Aquastop;
Anschluss mehrerer Leuchten durch Sternverdrahtung mit externem Erd-Abzweigkasten möglich

Lichtrichtung:




installation:
2 m connection cable (H05RN8-F 3G0,75) with aquastop;
possibility of connection of several luminaires by star wiring with external earth distribution box

light direction:



trittfest

walk-over resistant



Größe in mm
size in mm

Farbe colour		2700K 		3000K	
		Art.-Nr. item no.	Systemleistung system perform.	Art.-Nr. item no.	Systemleistung system perform.
	stainless steel Sicherheitsglas klar safety glass clear	91080-27	8 W/574 lm	91080	8 W/580 lm
	stainless steel black galvanisiert Sicherheitsglas getönt galvanized safety glass tinted	91080-27-BL	8 W/261 lm	91080-BL	8 W/270 lm

+ Anschluss optional mit IP44.de connect.
connection with IP44.de connect as an option.

Zubehör accessory	Artikel article	Art.-Nr. item no.
	Erd-Abzweigkasten earth distribution box	55380