



Soft Spun LED Small

Designed by Sebastian Wrong, 2010



LED - Top LED - 28WW - 1184lm - 3000K - CRI> 90

Wall recessed SOFT luminaire for LED lamp.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT



Main specifications

Mounting	Recessed
Enviroment	Indoor dry location
Light source type	LED
LED type	Top LED
Lamp category	LED
Lamp holder	LED Module
Ilcos	LED
Number of heads	1
Power (W)	28W
System power (W)	35
System flux (lm)	1184

Physical

Colodi	Naw
Trim	No
Orientation	Fixed
Recessed depth (mm)	35
Length (mm)	590
Net weight (kg)	11
IP	20
IP external	20

Download

Mounting instructions



Ecodesign and Energy Labelling



Non-replaceable light source



ΙP	
20	





https://professional.flos.com/en/global/product/soft-spun-led-small-sa.5006.1f/

SA.5006.1F

Photometric

Lighting type	Direct
Light distribution	Symmetric
CCT (K)	3000
CRI>	90

Electrical

Insulation class	I
Frequency (Hz)	50/60
Main voltage (Vac)	240
Alternating current voltage (Vac)	240
Driver	Remote included
Dimmable	No
Dimming type	Non Dimmable
Dimming interface	Not Dimmable
Emergency type	No