


LEDSTRIP PROFILES SMALL IP67 POTTED



| | | | |
|-------------|--------------------|--------------|---------------------------|
| GEAR/DRIVER | not included | MAX LENGTH | 6 000 mm (in one profile) |
| MATERIAL | Aluminium + Resine | MIN LENGTH | 50 mm |
| WEIGHT (KG) | 0.3 KG per meter | POWER SUPPLY | Constant voltage 12V DC |
| IP | IP67 | MAX POWER | 14.5W 2.04A per meter |
| BEAM ANGLE | 120° | SMD LEDS | 120 SMD LEDS per meter |
| CRI | 90 + | | |



OPTION: Possible options see Accessories. Excludes power cable (order separately).
Dimmable (cfr. Accessories)

SPECIAL: Ral colour per meter with Article No. :
LEDP SMPM RAL LACQ

CAUTION: The electrical connections must always be placed above the waterline.
A pull-through tube must also be provided for the cable from the fixture to above the waterline.

MODELS

| | ARTICLE N° | DESCRIPTION | COLOUR | LUMENOUTPUT |
|--|--------------------|---|---------------|----------------------------|
| | LEDW SMPM WWW 1CON | Ledprofile Small / Exterior / Warm White / 1 Connection / Max power 14.5W 1.21A per meter / 120 SMD LEDS per meter | 2700K | 660 lumen per meter |
| | LEDW SMPM WAW 1CON | Ledprofile Small / Exterior / Warm White / 1 Connection / Max power 14.5W 1.21A per meter / 120 SMD LEDS per meter | 3000K | 720 lumen per meter |
| | LEDW SMPM NAW 1CON | Ledprofile Small / Exterior / Natural White / 1 Connection / Max power 14.5W 1.21A per meter / 120 SMD LEDS per meter | 4000K | 792 lumen per meter |
| | LEDW SMPM COW 1CON | Ledprofile Small / Exterior / Cold White / 1 Connection / Max power 14.5W 1.21A per meter / 120 SMD LEDS per meter | 6000K | 900 lumen per meter |
| | LEDW SMPM CWW 1CON | Ledprofile Small / Exterior / Hybrid White / Max power 9.3W 0.8A per meter / 60 SMD LEDS per meter | 2700K - 6000K | 180-234 lumen per meter |
| | LEDW SMPM RGB 1CON | Ledprofile Small / Exterior / RGB / 1 Connection / Max power 14.5W 1.21A per meter / 60 SMD LEDS per meter | RGB | 234 lumen per meter |