





VISION S OUT 930 A

22312 9300 A

AVAILABLE IN

ALU GREY 22312 9300 A

ANTHRACITE (DARK GREY) 22312 9300 N



[View on website](#)

General info

LOCATION	outdoor
INSTALLATION	Wall Surface mounted
INGRESS PROTECTION	IP55
PROTECTION AGAINST MECHANICAL IMPACT	IK03
WEIGHT (KG)	0.8
ADJUSTABILITY	non adjustable
INFORMATION	INCL.1 x LENS INCL.LED POWER SUPPLY 500mA-DC

Electrical info

ELECTRICAL	120-240V / 50-60Hz
CLASS	II
POWER SUPPLY INCLUDED	YES
DIM TYPE	non-dimmable
ENERGY CLASS	E

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	2 x (LED cluster 1,4W / CRI>90 (R9: 60) / 3000K / 178lm)
TM-30 VALUES	Rf: 91 / Rg: 101
SDCM	SDCM3
RISKGROUP	RG2
LM80	L90B10 > 150000
LED TECHNICS (LIGHT SOURCE)	356lm // 2,8W // 127lm/W
LED TECHNICS (LUMINAIRE)	221lm // 3W // 69lm/W

For detailed installation instructions, please consult the manual: [22312_XXX0_HAND.pdf](#)



VISION S OUT 930 A

22312 9300 A

Notes: