



PIRRO on track

1-PHASE




2.0 SPOT

LED 2x LED COB 5W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium powder coated
PC lens and reflector
1-phase Global® track adapter

⊕ IP20 310° Δ 32° SDCM2 L70|55K 0.36kg

	CODE
	173264E_
	173264K_
	173264B_

LIGHT COLOUR	LUMEN CRI	CODE
2700K	2x360 >90	3
3000K	2x380 >90	5




4.0 SPOT

LED 4x LED COB 5W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium powder coated
PC lens and reflector
1-phase Global® track adapter

⊕ IP20 310° Δ 32° SDCM2 L70|55K 0.58kg

	CODE
	173464E_
	173464K_
	173464B_

LIGHT COLOUR	LUMEN CRI	CODE
2700K	4x360 >90	3
3000K	4x380 >90	5




2.0 OPAL

LED LED PCB 7W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium powder coated
PMMA cover | 1-phase Global®
track adapter

⊕ IP20 310° SDCM3 L80|60K 0.33kg

	CODE
	173284E_
	173284K_
	173284B_

LIGHT COLOUR	LUMEN CRI	CODE
2700K	270 >90	3
3000K	290 >90	5




4.0 OPAL

LED LED PCB 12W | phase-cut dim
220-240VAC | 50-60Hz | incl. driver
aluminium powder coated
PMMA cover | 1-phase Global®
track adapter

⊕ IP20 310° SDCM3 L80|60K 0.54kg

	CODE
	173484E_
	173484K_
	173484B_

LIGHT COLOUR	LUMEN CRI	CODE
2700K	710 >90	3
3000K	740 >90	5



white luminaires come with a white adapter | other colours are standard with black adapter