

CENO

SEMI RECESSED | CEILING RECESSED

1.0 SEMI RECESSED

LED COB 6W | 350mA | 17V
excl. driver
aluminium powder coated

IP20 0°-90°/350° A 31° SDCM2 L70I55K 0.14kg

	CODE
	176561W_
	176561B_

LIGHT COLOUR	LUMEN CRI	CODE
2700K	470 >90	3
3000K	500 >90	5

1.0

LED COB 6W | 350mA | 17V
excl. driver
aluminium powder coated

IP20 0°-90°/350° A 39° SDCM2 L70I55K 0.12kg

wire springs ⌀45-47 1.85 4-26

	CODE
	176161W_
	176161G_
	176161Q_
	176161K_
	176161CH_
	176161B_

LIGHT COLOUR	LUMEN CRI	CODE
2700K A 31°	470 >90	3
3000K A 31°	500 >90	5
2000-3000K 16V	355 >90	9

ALWAYS USE

see installation sheet for driver placement | 350mA

	CODE
10W dim	90223402
10W DALI	90243401



more options and specs on page 736

ALWAYS USE

driver | 350mA

	CODE
10W dim	90223402
10W DALI	90243401

more options and specs on page 736



OPTIONAL

honeycomb louver

	CODE
	90051131

more options and specs on page 736



201



261 | 299



487