

525033

Product Sheet

ares

THE OUTDOOR BY FLOS

ARES s.r.l - Socio Unico
v.le dell'Artigianato n.24 - 20881 Bernareggio - MB (Italy)
www.aresill.net - flos.outdoor@flos.com

Perseo


Adjustable projector for installation on wall or on pole. Configuration: die-cast aluminium structure. EN AB-47100 alloy (low copper content). Glass diffuser: extra-clear, fixed to the frame through a robotic gluing system. Double layer coating for high resistance to corrosion: the aluminium components are painted with a double coat using powders which are compliant with QUALICOAT standards: a first layer of epoxy powder (with excellent chemical and mechanical resistance) and a second finishing layer of polyester powder (resistant to UV rays and atmospheric agents). The entire painting process of the aluminium fitting starts from components which have been sand-blasted in advance to make the surface more porous and increase the adherence of the paint. Ares effects alkaline and acid washing to clean the surfaces completely, then rinses with demineralised water to remove any residue particles, subsequently a chemical conversion treatment is done to protect against rusting. Protection rating: IP65. In compliance with EN60598-1 standards. Class of insulation: I. Installation: wiring through an M16x1.5 metal cable gland (4,5mm- ϕ <10mm cables). Outdoor use requires suitable flexible cables assuring the watertightness of the cable gland.

IP65   

Available Colors for this Version



Perseo9 Mid-Power LED / Adjustable - Sandblasted Glass



Warnings

Projector



Floor installation



The fitting is equipped with 1 cable input



Wall fitting



Protection against impact. IK 07 - 02,00 joule

Pole Top



Installation on pole



Protection against impact. IK 07 - 02,00 joule



The fitting is equipped with 1 cable input

Product Code Details

525033

Light Source



WARM WHITE 3000K MID-POWER LEDs 8,8W/220÷240V

Total power 11W

LED lm 1198 ÷ OUTPUT lm 624

CRI>80

Integral electronic power supply

Light Flux, Placement



A A+ A++

Accessories



Code: 136
Ground spike
H 200 mm



Code: 161
Wall bracket
300 mm



Code: 162
Wall bracket
600 mm




Code: 177
ø48 - Poles with Base
H 500 mm
Combinable with Base plate and fixing bolts,
code 182



Code: 178
ø48 - Poles with Base
H 800 mm
Combinable with Base plate and fixing bolts,
code 182



Code: 182
Base plate and fixing bolts
Ø 110 x H 160 mm



Code: 237
SPD: (Surge Protection Device) 275Vac
Maximum discharge current 10KA (8/20µs)
Maximum operating current 5A
Suitable for series connection - IP66