



ENTERO SQ-M IP SOFT 93030 GC



28515 9020 GC

AVAILABLE IN

BLACK 28515 9020 B

GOLD COLOURED 28515 9020 GC

WHITE 28515 9020 W



 [View on website](#)

General info

LOCATION	indoor
INSTALLATION	Ceiling Recessed
CUTOUT SHAPE/SIZE (MM)	square - 92 x 92
RECESSED DEPTH (MM)	145
THICKNESS OF MOUNTING SURFACE (MM)	12,5 or 25
INGRESS PROTECTION	IP44/20
WEIGHT (KG)	0.42
ADJUSTABILITY	0° to 20° swiveling, 355° rotatable
INFORMATION	REFLECTOR FL-30° EXCL.DIMMABLE LED POWER SUPPLY 450mA-DC

Electrical info

CLASS	III
DIM TYPE	depending on type of external power supply
ENERGY CLASS	F
CERTIFICATES	CB, ENEC

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 16,1W / CRI>90 (R9: 50) / 3000K-1800K / 1618lm
TM-30 VALUES	Rf: 90 / Rg: 99
SDCM	SDCM2
RISKGROUP	RG1
LM80	L90B10 > 50000
LED TECHNICS (LIGHT SOURCE)	1618lm // 16,1W // 101lm/W
LED TECHNICS (LUMINAIRE)	1054lm // 19W // 57lm/W

Requirements


LED POWER SUPPLY 450mA-DC DIM

For detailed installation instructions, please consult the manual: [28515_XXX0_HAND.pdf](#)

ENTERO SQ-M IP SOFT 93030 GC

28515 9020 GC

CEILING COMPATIBILITY


Ceiling Type	Mounting Kit
	System ceiling -
	Plasterboard -
	Stucanet -
	Wood -
	Stretched ceiling -

ENTERO SQ-M IP SOFT 93030 GC

28515 9020 GC


LED power supplies

#




300 90 68 LED POWER SUPPLY MULTI-POWER DIM5

1(0)




300 90 124 LED POWER SUPPLY MULTI-POWER DIM7

1(0)




300 90 125 LED POWER SUPPLY MULTI-POWER MINI DIM5

1(0)




21012 005W LED POWER SUPPLY MULTI-POWER COMPACT WDL

1




21012 0298 LED POWER SUPPLY MULTI POWER 250-900 / 20W DIM8

1




21012 0420 LED POWER SUPPLY MULTI POWER 250-1000mA-DC / 35W

1(1)



21012 0431 LED POWER SUPPLY MULTI POWER 250-1000mA-DC / 35W DIM1

1(1)



21012 0445 LED POWER SUPPLY MULTI POWER 250-1000mA-DC / 35W DIM5

1(1)

Notes:

 DELTALIGHT®

ENTERO SQ-M IP SOFT 93030 GC

28515 9020 GC