



ENTERO SQ-M IP TW 96518 W



28516 9010 W

AVAILABLE IN

BLACK 28516 9010 B

GOLD COLOURED 28516 9010 GC

WHITE 28516 9010 W



 [View on website](#)

General info

LOCATION	indoor
INSTALLATION	Ceiling Recessed
CUTOUT SHAPE/SIZE (MM)	square - 92 x 92
RECESSED DEPTH (MM)	145
THICKNESS OF MOUNTING SURFACE (MM)	12,5 or 25
INGRESS PROTECTION	IP44/20
WEIGHT (KG)	0.42
ADJUSTABILITY	0° to 20° swiveling, 355° rotatable
INFORMATION	REFLECTOR SP-18° EXCL.LED POWER SUPPLY 500mA-DC TW - (DALI DT8)

Electrical info

CLASS	III
DIM TYPE	depending on type of external power supply
ENERGY CLASS	E
CERTIFICATES	CB, ENEC

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 9W / CRI>90 (R9: 50) / 2700K-6500K / 1087lm
TM-30 VALUES	Rf: 89 / Rg: 100
SDCM	SDCM2
RISKGROUP	RG1
LM80	L90B10 > 50000
LED TECHNICS (LIGHT SOURCE)	1087lm // 9W // 121lm/W
LED TECHNICS (LUMINAIRE)	708lm // 10W // 68lm/W

Requirements


LED POWER SUPPLY 500mA-DC TW

For detailed installation instructions, please consult the manual: [28516_XXX0_HAND.pdf](#)

ENTERO SQ-M IP TW 96518 W


28516 9010 W

CEILING COMPATIBILITY

Ceiling Type	Mounting Kit
 System ceiling	-
 Plasterboard	-
 Stucanet	-
 Wood	-
 Stretched ceiling	-

FINISH YOUR SPECIFICATION

LED power supplies



21012 0355 LED POWER SUPPLY 500mA-DC 2CH TW DIM5

1->2

Notes: