



ENTERO RD-M X 92730 B

28443 9220 B



AVAILABLE IN

BLACK 28443 9220 B

FLEMISH BRONZE OUTDOOR 28443 9220 FBRX

ANTHRACITE (DARK GREY) 28443 9220 N

WHITE 28443 9220 W



 [View on website](#)

General info

LOCATION	outdoor
INSTALLATION	Ceiling Recessed
CUTOUT SHAPE/SIZE (MM)	round - 92
RECESSED DEPTH (MM)	140
THICKNESS OF MOUNTING SURFACE (MM)	max.16
INGRESS PROTECTION	IP65
PROTECTION AGAINST MECHANICAL IMPACT	IK06
WEIGHT (KG)	0.46
ADJUSTABILITY	0° to 20° swiveling, 355° rotatable
INFORMATION	REFLECTOR FL-30° EXCL.LED POWER SUPPLY 350-500mA-DC

Electrical info

CLASS	III
DIM TYPE	depending on type of external power supply
ENERGY CLASS	E
CERTIFICATES	CB, ENEC, EPD

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 11,6-17,2W / CRI>90 (R9: 60) / 2700K / 1458-2009lm
TM-30 VALUES	Rf: 89 / Rg: 100
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
LED TECHNICS (LIGHT SOURCE)	2009lm // 17,2W // 117lm/W
LED TECHNICS (LUMINAIRE)	1233lm // 20W // 62lm/W

Requirements

LED POWER SUPPLY 350 / 500mA-DC DIM

Options

ENTERO RD-M MOUNTING SET S2

ENTERO RD-M X 92730 B













28443 9220 B

Accessories

ENTERO M HONEYCOMB
 ENTERO M LINEAR SPREAD LENS
 ENTERO M SPREAD LENS
 ENTERO M SOFTENING LENS
 ENTERO M GLASS SBL

For detailed installation instructions, please consult the manual: [28443_XXXO_HAND.pdf](#)

CEILING COMPATIBILITY


Ceiling Type	Mounting Kit
 System ceiling	-
 Plasterboard	-
 Stucanet	-
 Wood	-
 Concrete	 ENTERO RD-M MOUNTING SET S2 Required
 Concrete + plaster	 ENTERO RD-M MOUNTING SET S2 Required
 Lintel + plaster	 ENTERO RD-M MOUNTING SET S2 Required
 Hollow-core slab	 ENTERO RD-M MOUNTING SET S2 Required
 Hollow-core slab + plaster	 ENTERO RD-M MOUNTING SET S2 Required
 Stretched ceiling	-

ENTERO RD-M X 92730 B

28443 9220 B


LED power supplies

#




300 90 63 LED POWER SUPPLY MULTI-POWER DIM9

1->2(2) / 1->2(2)




300 90 68 LED POWER SUPPLY MULTI-POWER DIM5

1(1) / 1(0)



300 90 69 LED POWER SUPPLY MULTI-POWER HV DIM9

1->3(3) / 1->3(2)




300 90 124 LED POWER SUPPLY MULTI-POWER DIM7

1(1) / 1(0)




300 90 125 LED POWER SUPPLY MULTI-POWER MINI DIM5

1(1) / 1(0)




21012 0010 LED POWER SUPPLY MULTI POWER

1/1




21012 0021 LED POWER SUPPLY MULTI POWER DIM1

1/1



21012 0035 LED POWER SUPPLY MULTI POWER DIM5

1/1




21012 005W LED POWER SUPPLY MULTI-POWER COMPACT WDL

1/1


ENTERO RD-M X 92730 B

28443 9220 B




21012 0268 LED POWER SUPPLY MULTI POWER 200-350 / 15W DIM8

1




21012 0288 LED POWER SUPPLY MULTI POWER 500-700 / 36W DIM8

1




21012 0298 LED POWER SUPPLY MULTI POWER 250-900 / 20W DIM8

1/1



21032 0295 LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM5

1




21032 0305 LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W DIM5

1


ENTERO RD-M X 92730 B

28443 9220 B


Light altering devices




28500 0070 ENTERO M LINEAR SPREAD LENS




28500 0080 ENTERO M SPREAD LENS



28500 0090 ENTERO M SOFTENING LENS




28500 0100 ENTERO M GLASS SBL



28500 0110 B ENTERO M HONEYCOMB SINGLE USE B

Mounting set S2



28500 0200 ENTERO RD-M MOUNTING SET S2

Notes: