



ENTERO RD-M X SOFT 93018 B

28444 9010 B



AVAILABLE IN

BLACK 28444 9010 B

FLEMISH BRONZE OUTDOOR 28444 9010 FBRX

ANTHRACITE (DARK GREY) 28444 9010 N

WHITE 28444 9010 W



 [View on website](#)

General info

LOCATION	outdoor
INSTALLATION	Ceiling Recessed
CUTOUT SHAPE/SIZE (MM)	round - 92
RECESSED DEPTH (MM)	140
THICKNESS OF MOUNTING SURFACE (MM)	max.16
INGRESS PROTECTION	IP65
PROTECTION AGAINST MECHANICAL IMPACT	IK06
WEIGHT (KG)	0.46
ADJUSTABILITY	0° to 20° swiveling, 355° rotatable
INFORMATION	REFLECTOR SP-18° EXCL.DIMMABLE LED POWER SUPPLY 450mA-DC

Electrical info

CLASS	III
DIM TYPE	depending on type of external power supply
ENERGY CLASS	F
CERTIFICATES	CB, ENEC

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 16,1W / CRI>90 (R9: 50) / 3000K-1800K / 1618lm
TM-30 VALUES	Rf: 90 / Rg: 99
SDCM	SDCM2
RISKGROUP	RG1
LM80	L90B10 > 50000
LED TECHNICS (LIGHT SOURCE)	1618lm // 16,1W // 101lm/W
LED TECHNICS (LUMINAIRE)	983lm // 19W // 53lm/W

Requirements

LED POWER SUPPLY 450mA-DC DIM

Options

ENTERO RD-M MOUNTING SET S2

ENTERO RD-M X SOFT 93018 B













28444 9010 B

Accessories

ENTERO M HONEYCOMB
 ENTERO M LINEAR SPREAD LENS
 ENTERO M SPREAD LENS
 ENTERO M SOFTENING LENS
 ENTERO M GLASS SBL

For detailed installation instructions, please consult the manual: [28444_XXXO_HAND.pdf](#)

CEILING COMPATIBILITY


Ceiling Type	Mounting Kit
 System ceiling	-
 Plasterboard	-
 Stucanet	-
 Wood	-
 Concrete	 ENTERO RD-M MOUNTING SET S2 Required
 Concrete + plaster	 ENTERO RD-M MOUNTING SET S2 Required
 Lintel + plaster	 ENTERO RD-M MOUNTING SET S2 Required
 Hollow-core slab	 ENTERO RD-M MOUNTING SET S2 Required
 Hollow-core slab + plaster	 ENTERO RD-M MOUNTING SET S2 Required
 Stretched ceiling	-

ENTERO RD-M X SOFT 93018 B

28444 9010 B

FINISH YOUR SPECIFICATION

Emergency units



21032 0270 B EMERGENCY UNIT 7W / 1h + LED INDICATOR HOLDER B


21032 0270 W EMERGENCY UNIT 7W / 1h + LED INDICATOR HOLDER W

ENTERO RD-M X SOFT 93018 B

28444 9010 B


LED power supplies

#




300 90 68 LED POWER SUPPLY MULTI-POWER DIM5

1(0)




300 90 124 LED POWER SUPPLY MULTI-POWER DIM7

1(0)




300 90 125 LED POWER SUPPLY MULTI-POWER MINI DIM5

1(0)




21012 005W LED POWER SUPPLY MULTI-POWER COMPACT WDL

1




21012 0298 LED POWER SUPPLY MULTI POWER 250-900 / 20W DIM8

1




21012 0420 LED POWER SUPPLY MULTI POWER 250-1000mA-DC / 35W

1(1)



21012 0431 LED POWER SUPPLY MULTI POWER 250-1000mA-DC / 35W DIM1

1(1)




21012 0445 LED POWER SUPPLY MULTI POWER 250-1000mA-DC / 35W DIM5

1(1)


ENTERO RD-M X SOFT 93018 B

28444 9010 B


Light altering devices




28500 0070 ENTERO M LINEAR SPREAD LENS




28500 0080 ENTERO M SPREAD LENS



28500 0090 ENTERO M SOFTENING LENS




28500 0100 ENTERO M GLASS SBL



28500 0110 B ENTERO M HONEYCOMB SINGLE USE B

Mounting set S2



28500 0200 ENTERO RD-M MOUNTING SET S2

Notes: