



ENTERO RD-M X TW 94018 W

28471 9010 W



AVAILABLE IN

BLACK 28471 9010 B

FLEMISH BRONZE OUTDOOR 28471 9010 FBRX

ANTHRACITE (DARK GREY) 28471 9010 N

WHITE 28471 9010 W



[View on website](#)

General info	
LOCATION	outdoor
INSTALLATION	Ceiling Recessed
CUTOUT SHAPE/SIZE (MM)	round - 92
RECESSED DEPTH (MM)	140
THICKNESS OF MOUNTING SURFACE (MM)	max.16
INGRESS PROTECTION	IP65
PROTECTION AGAINST MECHANICAL IMPACT	IK06
WEIGHT (KG)	0.46
ADJUSTABILITY	0° to 20° swiveling, 355° rotatable
INFORMATION	REFLECTOR SP-18° EXCL.LED POWER SUPPLY 500mA-DC TW - (DALI DT8)
Electrical info	
CLASS	III
DIM TYPE	depending on type of external power supply
ENERGY CLASS	E
CERTIFICATES	CB, ENEC
Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 9W / CRI>90 (R9: 50) / 1800K-4000K / 979lm
TM-30 VALUES	Rf: 89 / Rg: 100
SDCM	SDCM2
RISKGROUP	RG1
LM80	L90B10 > 50000
LED TECHNICS (LIGHT SOURCE)	979lm // 9W // 109lm/W
LED TECHNICS (LUMINAIRE)	595lm // 10W // 57lm/W

Requirements

LED POWER SUPPLY 500mA-DC TW

Options

ENTERO RD-M MOUNTING SET S2

ENTERO RD-M X TW 94018 W













28471 9010 W

Accessories

ENTERO M HONEYCOMB
 ENTERO M LINEAR SPREAD LENS
 ENTERO M SPREAD LENS
 ENTERO M SOFTENING LENS
 ENTERO M GLASS SBL

For detailed installation instructions, please consult the manual: [28471_XXX0_HAND.pdf](#)

CEILING COMPATIBILITY

Ceiling Type	Mounting Kit
 System ceiling	-
 Plasterboard	-
 Stucanet	-
 Wood	-
 Concrete	 ENTERO RD-M MOUNTING SET S2 Required
 Concrete + plaster	 ENTERO RD-M MOUNTING SET S2 Required
 Lintel + plaster	 ENTERO RD-M MOUNTING SET S2 Required
 Hollow-core slab	 ENTERO RD-M MOUNTING SET S2 Required
 Hollow-core slab + plaster	 ENTERO RD-M MOUNTING SET S2 Required
 Stretched ceiling	-


ENTERO RD-M X TW 94018 W

28471 9010 W

FINISH YOUR SPECIFICATION

LED power supplies


#




21012 0355 LED POWER SUPPLY 500mA-DC 2CH TW DIM5

1->2


Light altering devices




28500 0070 ENTERO M LINEAR SPREAD LENS




28500 0080 ENTERO M SPREAD LENS



28500 0090 ENTERO M SOFTENING LENS




28500 0100 ENTERO M GLASS SBL



28500 0110 B ENTERO M HONEYCOMB SINGLE USE B

Mounting set S2



28500 0200 ENTERO RD-M MOUNTING SET S2



ENTERO RD-M X TW 94018 W

28471 9010 W

Notes: